



Power **6,5-20 W**

Voltage **230 V**

Colour temperature **3000 K**

Light colour **WW**


Beam angle **36, 60 °**

Protection class **IP20**



See more on dedicated page 



 User manual



 Photometric file

Technical data:

Product code	SLI033023WW_PW
Power	6,5-20 W
Nominal current	90 mA
Voltage	230 V
Energy consumption	20 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	2300 lm (360°)
Luminous flux**	600-1700 lm (360°)
Light efficiency	115 lm/W
Luminous intensity	3800 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	36, 60 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	Black
Dimension (axbxc)	75x78x110 mm
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



\*Applies to the LED source used. \*\*Luminaire luminous flux