




CE

Power	19-42 W	Voltage	230 V
Colour temperature	3000 K	Light colour	WW
Beam angle	20-45 °	Protection class	IP20



See more on dedicated page [➔](#)




 User manual



 Declaration of Conformity

Technical data:

Product code	SLI033030WW_PW
Power	19-42 W
Nominal current	185 mA
Voltage	230 V
Energy consumption	42 kWh/1000h
Frequency	50HZ Hz
Protection class	II
Power supply included	Yes
Power factor	0.9
Useful luminous flux*	4500 lm (360°)
Luminous flux**	1600-3000 lm (360°)
Light efficiency	107 lm/W
Luminous intensity	8900 cd
Colour temperature	3000 K
Light colour	WW
Beam angle	20-45 °
RA	>90
Light source included	Yes
Uniformity of color SDCM max	5
Dimmable	No
Working temperature range	-20/+40 °
Lifespan	50000 h
Housing material	Aluminum, PLASTIC
Protection class	IP20
Colour	White
Dimension (axbxc)	96x192x231 mm
Weight	1.2 kg
For use	Inside
Assembly method	On 3-circuit system
Application	Inside
Made in	PRC
Other	DIP SWITCH - regulowana moc oprawy ,



*Applies to the LED source used. **Luminaire luminous flux